

# Rechargeable Sealed Lead-Acid Battery

## PS-610

### 6 Volt 1.1 Amp. Hrs.



**Features:**


- Absorbent Glass Mat (AGM) technology for superior performance.
- Valve regulated, spill proof construction allows safe operation in any position.
- Power/volume ratio yielding unrivaled energy density.
- Rugged ABS plastic case and cover
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified.
- U.L. recognized under file number MH 47566.




**PERFORMANCE SPECIFICATIONS**

<b>Nominal Voltage</b> .....	6 volts (3 cells in series)
<b>Nominal Capacity</b>	
20 hour rate (55mA to 5.25 volts) .....	1.1 A.H.
10 hour rate (100mA to 5.25 volts) .....	1.0 A.H.
5 hour rate (190mA to 5.10 volts) .....	0.95 A.H.
1 hour rate (680mA to 4.50 volts) .....	0.68 A.H.
<b>Approximate Weight</b> .....	0.6 pounds (0.3 kg)
<b>Energy Density (20 hour rate)</b> .....	1.0 Watt-hours/cubic inch (54.9 Watt-hours/l)
<b>Specific Energy (20 hour rate)</b> .....	9.5 Watt-hours/pound (20.7 Watt-hours/kg)
<b>Internal Resistance (Fully Charged Battery)</b> .....	110 milliohms (approximately)
<b>Maximum Discharge Current ( ≤ 7 Min.)</b> .....	3 amperes
<b>Maximum Short-Duration Discharge Current ( ≤ 10 Sec.)</b> .....	10 amperes
<b>Terminals</b> .....	"F1": Quick disconnect tabs, 0.187" x 0.032" - Mate with AMP. INC. FASTON "187" series
<b>Shelf Life — % of nominal capacity at 68° F (20° C)</b>	
1 Month.....	97%
3 Months.....	91%
6 Months.....	83%
<b>Operating Temperature Range</b>	
<b>Charge</b> .....	-4°F (-20°C) to 122°F (50°C)
<b>Discharge</b> .....	-4°F (-20°C) to 140°F (60°C)
<b>Case</b> .....	ABS Plastic


**Shelf Life and Storage**




**Discharge Characteristics**




**Life Characteristics in Stand-By Use**



**Discharge Time vs. Discharge Current**



**Life Characteristics in Cyclic Use**



**CHARGING**





**Cycle Applications:** Limit initial current to 300mA. Charge until battery voltage (under charge) reaches 7.20 to 7.35 volts at 68°F (20°C). Hold at 7.20 to 7.35 volts until current drops to approximately 11mA. Battery is fully charged under these conditions, and charger should either be disconnected or switched to "float" voltage.

**"Float" or "Stand-By" Service:** Hold battery across constant voltage source of 6.75 to 6.90 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

**NOTE:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged after 6-9 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

Physical Dimensions: in. (mm)

Terminals: F1 (mm)



Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.